



Ai-M62-32S

Power Consumption Test Report

1. Test Description

1.1 Test Instruments

Instrument	Manufacturer	Model
Current Analyzer	KEYSIGHT	N6705C

1.2 Test Conditions

Item	Condition	Note
Power Input	3.3V	/
Temperature	25°C (Room temperature)	/

1.3 Test Items

Item	Result	Note
Power Consumption Test	PASS	/

1.4 Other Notes

Tested by	Qiao Rongxin	Note
Reviewed by	Guan Ning	/
Test Date	2024-09-23	/

Test Mode		Min	Avg	Max	Unit
11b TX	CCK 11 Mbps, Pout = +23 dBm, Duty 50%	-	271.48	-	mA
	CCK 11 Mbps, Pout = +23 dBm, Duty 100%	-	347.65	-	mA
11g TX	OFDM 54 Mbps, POUT = +19 dBm, Duty 50%	-	212.97	-	mA
	OFDM 54 Mbps, POUT = +19 dBm, Duty 100%	-	299.78	-	mA
11n TX	OFDM MCS7, POUT = +19 dBm, Duty 50%	-	215.18	-	mA
	OFDM MCS7, POUT = +19 dBm, Duty 100%	-	300.16	-	mA
11b RX	802.11b Sensitivity 1 Mbps	-	59.1	-	mA
	802.11b Sensitivity 11 Mbps	-	59.1	-	mA
11g RX	802.11g Sensitivity 6 Mbps	-	59.1	-	mA
	802.11g Sensitivity 54 Mbps	-	59.1	-	mA
11n RX	802.11n Sensitivity MCS0	-	59.1	-	mA
	802.11n Sensitivity MCS7	-	59.1	-	mA
Low Power Consumption	DTIM10 (with DCDC and RTC crystal)	-	128	-	μA