



Ai-WV02-32S

Power Consumption Test Report

1. Test Description

1.1 Test Instrument

Instrument	Manufacturer	Model
Current Analyzer	KEYSIGHT	N6705C

1.2 Test Conditions

Item	Condition	Note
Power Input	3.3V	/
Temperature	25°C (Room Temperature)	/

1.3 Test Items

Item	Result	Note
Power Consumption Test	PASS	/

1.4 Other Notes

Tested by	Lv Xihuan	Note
Reviewed by	Guan Ning	/
Test Date	2025-09-09	/

Test Mode		Min	Avg	Max	Unit
11b TX	CCK 11 Mbps, Pout = +22 dBm, Duty 50%	-	247	-	mA
	CCK 11 Mbps, Pout = +22 dBm, Duty 100%	-	419.08	-	mA
11g TX	OFDM 54 Mbps, POUT = +19 dBm, Duty 50%	-	203.11	-	mA
	OFDM 54 Mbps, POUT = +19 dBm, Duty 100%	-	328	-	mA
11n TX	OFDM MCS7, POUT = +19 dBm, Duty 50%	-	203.03	-	mA
	OFDM MCS7, POUT = +19 dBm, Duty 100%	-	326.52	-	mA
11ax TX	OFDM MCS9, POUT = +17 dBm, Duty 50%	-	185.32	-	mA
	OFDM MCS9, POUT = +17 dBm, Duty 100%	-	294.3	-	mA
11b RX	802.11b Sensitivity 1 Mbps	-	92	-	mA
	802.11b Sensitivity 11 Mbps	-	94	-	mA
11g RX	802.11g Sensitivity 6 Mbps	-	92	-	mA
	802.11g Sensitivity 54 Mbps	-	92	-	mA
11n RX	802.11n Sensitivity MCS0	-	92	-	mA
	802.11n Sensitivity MCS7	-	92	-	mA
11ax TX	802.11ax Sensitivity MCS0	-	92	-	mA
	802.11ax Sensitivity MCS9	-	92	-	mA